







PRODUCT NUMBERING SYSTEM

S1300H - HD1 - 230

MOUNTING OPTIONS	PHASE	VOLTAGE	ADDITIONAL OPTIONS
H: Horizontal Tank V: Vertical Tank	1: Single Phase 3: Three Phase	230 (208/230V) 460	S: Prewired Magnetic Starter U: 30-40 psi Pressure Switch (Also available in PU and SU)



- ✓ Built for longevity
- ✓ Appropriate for single or multiple-valve systems
- ✓ Great for older sprinkler systems
- ✓ Low cost of ownership
- ✓ 12-month unit warranty
- ✓ 3-year pump warranty
- ✓ Tank drain, large oil sight glass, and full synthetic oil included
- ✓ Compatible with all regulator air maintenance devices
- ✓ Vibration absorbing feet included
- ✓ 2D & 3D CAD files available
- ✓ UL & CSA Listed

SYSTEM SIZE	PSI	GAL.	TECHNICAL SPECIFICATIONS		ACCESSORIES AVAILABLE
Pre-Action	10	6356	HP	5	 1/2" x 30" stainless steel flexible hose Part: DT 3005 H-1PK Pack of 5: PART DT 3005 H-5PK
Low Pressure	18	3308	PRESSURE SWITCH	On @ 70 PSI, OFF @ 100 PSI Optional 30-40 PSI	
Standard Pressure	40	1394	CFM	17.91 @ 10 PSI	
			PUMP	2 Cylinder	 1/2" x 36" flexible hose Part: DT 3605 H Pack of 5: PART DT 3605 H-5PK
			CYLINDERS	Cast Iron	
			OUTLET	1/2" NPT	 1/2" x 48" flexible hose Part: DT 4805 H Pack of 5: PART DT 4805 H-5PK
			DIMENSIONS	50" x 24" x 43" Horizontal 33" x 23" x 70" Vertical	
			WEIGHT	490 lbs.	 1/2" x 72" flexible hose Part: DT 7205 H Pack of 5: PART DT 7205 H-5PK
			TANK SIZE	60 Gallon Horizontal 60 Gallon Vertical	
ELECTRICAL SPECIFICATIONS					
PHASE/ VOLTS	RUNNING AMPS	BREAKER SIZE			
1/230	25.8	40 Amp			
3/230	14.6	20 Amp			
3/460	7.28	15 Amp			