



**QUIET  
LOW RPM  
QUALITY**








PRODUCT NUMBERING SYSTEM

## A015V060-1115

HORSEPOWER	TANK ORIENTATION	TANK SIZE	PHASE	VOLTAGE
015: 1.5 HP	V: Vertical	060: 60 Gal	1: Single	115 230



- ✓ Built to last with premium parts
- ✓ Low RPM pump to decrease noise level
- ✓ Low cost of ownership
- ✓ 12-month warranty included
- ✓ Tank drain, ball valve, oil drain tube, and full synthetic oil included
- ✓ Large oil sight glass and liquid filled gauge included

UNIT SPECIFICATIONS			DESCRIPTION	ACCESSORIES AVAILABLE	
HP	1.5		The C-Aire 1.5 HP 60 Gallon Simplex unit features a low-RPM cast iron pump with an aluminum head for efficient cooling, Sandvik Swedish steel reed valves, finned intercooler tubes, and an easy-to-read oil sight glass. It also has a large frame heavy-duty motor to ensure reliable performance and long life.		<b>Installation Kit</b> Part: Install-60V
TANK SIZE	60 Gallon				<b>Electronic Tank Drain Kit</b> Part: EL CRDV-177K
DIMENSIONS	30" x 23" x 68"				<b>1/2" x 12" Stainless Steel Flex Hose</b> Part: DT 1005 H
SHIPPING WEIGHT	260 lbs.				<b>1/2" x 30" Stainless Steel Flex Hose</b> Part: DT 3005 H
PUMP SPECIFICATIONS			<p><b>SUITABLE FOR:</b></p> <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="text-align: center;">  <p>HOME USE</p> </div> <div style="text-align: center;">  <p>HOBBYIST</p> </div> </div> <p>▼ NEXT SIZE DOWN: P016V030-1115      ▲ NEXT SIZE UP: A030V060-1230</p>		<b>Synthetic Compressor Oil</b> Part: LU 1082 GAL/LU 1082 QT
STAGE	1				
CFM @ 90 PSI	7.2				
PUMP	2 Cylinder Cast Iron				
PUMP RPM	742				
MAIN BEARINGS	50,000 Hour				
OIL	Full Synthetic				
MOTOR SPECIFICATIONS					
MOTOR RPM	3450				
PHASE/VOLTS	RUNNING AMPS	BREAKER SIZE			
1/115	17.4	30 Amp			
1/230	8.8	15 Amp			