



**QUIET
LOW RPM
QUALITY**

PRODUCT NUMBERING SYSTEM

A 150H 120-3 230

HORSEPOWER	TANK ORIENTATION	TANK SIZE	PHASE	VOLTAGE	UPGRADE OPTIONS
150: 15 HP	H: Horizontal	120: 120 Gal	3: Three	230 460	FP: Fully Packaged Includes: - Aftercooler - Automatic Tank Drain - Installation Kit



- ✓ **Built to last with premium parts**
- ✓ **Low RPM pump to decrease noise level**
- ✓ **Low cost of ownership**
- ✓ **12-month warranty included**
- ✓ **3-year extended warranty available**
- ✓ **Tank drain, ball valve, oil drain tube, and full synthetic oil included**
- ✓ **Large oil sight glass and liquid filled gauge included**

UNIT SPECIFICATIONS

HP	15
TANK SIZE	120 Gallon
DIMENSIONS	76" x 29" x 54"
SHIPPING WEIGHT	885 lbs.

PUMP SPECIFICATIONS

STAGE	2
CFM @ 175 PSI	50
PUMP	3 Cylinder Cast Iron
PUMP RPM	845
MAIN BEARINGS	50,000 Hour
OIL	Full Synthetic

MOTOR SPECIFICATIONS

MOTOR RPM	RUNNING AMPS	BREAKER SIZE
3/230	42.8	70 Amp
3/460	21.4	30 Amp

FULLY PACKAGED UPGRADE OPTION

- **OVERSIZED AFTERCOOLERS**
 - Remove over 60% of water vapor, humidity, or moisture.
- **ENERGY SAVING PNEUMATIC AUTOMATIC TANK DRAIN**
 - Drains condensate with zero air loss every time the compressor shuts off.
 - Prevents valves from fouling and reduces corrosion.
- **INCLUDES INSTALLATION KIT**
 - 4 mounting pads
 - 4 anchor bolts
 - 12" steel braided flex hose

SUITABLE FOR:



▼ **NEXT SIZE DOWN:**
A100V120-3230

▲ **NEXT SIZE UP:**
A150H240-3230

ACCESSORIES AVAILABLE

- Installation Kit**
Part: Install-120
- 3-Year Extended Warranty Kit**
Part: AX-W115 / AX-K60
- Electronic Tank Drain Kit**
Part: EL CRDV-177K
- 1/2" x 12" Stainless Steel Flex Hose**
Part: DT 1005 H
- 1/2" x 30" Stainless Steel Flex Hose**
Part: DT 3005 H
- Synthetic Compressor Oil**
Part: LU 1082 GAL/LU 1082 QT