

ROTARY SCREW CL SERIES

C4L
C5L
C7L
C10L
C15L
C20L

SPECIFICATIONS

CFM	11	14	30	37	67	77
Horsepower	4	5.5	7.5	10	15	20
Tank Size Options (Gallons)	80	80	80	120	120 / 240*	120 / 240*
Max Pressure (PSIG)	150	150	125	150	150	150
Noise Level (dB)	65	65	69	68 / 65**	79 / 69**	79 / 69**
Mounting Options***	B, T, D	B, T, D	B, T, D	B, T, D	B, T, D	B, T, D
Weight (lbs.)	904	937	968	1130	1218	1218
Dimensions (W x D x H)	66"x29"x49"	66"x29"x49"	66"x29"x49"	79"x34"x60"	84"x34"x60"	84"x34"x60"
Product Number	BEC4L	BEC5L	BEC7L	BEC10L	BEC15L	BEC20L

ADD-ONS

Refrigerated Dryer	KRAD 25	KRAD 25	KRAD 40	KRAD 40	KRAD 80	KRAD 80
Air Filtration	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Ball Valve Tank Drain Included	✓	✓	✓	✓	✓	✓
Electronic Tank Drain Available	✓	✓	✓	✓	✓	✓
Oil/Water Separator	Qwick-Pure 25	Qwick-Pure 25	Qwick-Pure 25	Qwick-Pure 25	Qwick-Pure 25	Qwick-Pure 25
Three-Valve Bypass	✓	✓	✓	✓	✓	✓
Sound Enclosure Available				✓	✓	✓

VOLTAGE / PHASE

208 / 1		✓	✓			
230 / 1		✓	✓			
230 / 3 w/Prewired Magnetic Starter	✓	✓	✓	✓	✓	✓
460 / 3 w/Prewired Magnetic Starter	✓	✓	✓	✓	✓	✓

*240 gallon tank required for sound enclosure add-on

**With sound enclosure add-on

***B=Base Mounted; T=Tank Mounted; D=Tank w/Refrigerated Dryer